



## **TYPICAL BASEMENT PLAN**

BASEMENT PLAN - AREA = 1423 + UNFINISHED.





SECTION A-A

SPECIFICATIONS

CAPAGE FOUNDATION
CAPAGE FOUNDATION
CAPAGE FOUNDATION
CAPAGE FOUNDATION
CAPAGE FOUNDATION

2) GAPAGE SLAD ON 6 MIL POUT ON COMPACTED CRAVEL

(2) EXTERIOR WALL EXTERIOR FINISH ON 36, 000 SHEATHING ON SAG SPE STORN 62.000 00. - 500 0000 E0000 E0000 00

(4) FOUNDATION WALL & CAPAGE A MUL PUT MONSTORE PARELER AN 5, PAF PLYLOOD ON 21 AS THAF HALFLY ANDROB [21 AC. - 548, AC. - 548, AC. - 248, AC. - 248, AC. - 248, AC. - 248, AC. - 244, PAFE JUNA CAPACE ON A MUL PROVING AND A PLACE IN - 244, PAFE JUNA REAL ADD. - 201 21 X.28 FOOTHER FUNDE - 244, PAFE JUNA REAL OL. OU 21 X.28 FOOTHER FUNDE - 244, PAFE JUNA

() EASEMENT SLAD

PUN OU 5' GRANULAR DRAILAGE LAVER C MAIN FLOOR

JOSTSE FLOOR ON 36" THE FIR PRIVED ON 2"NO"

Koptal defined of 1/2, 000 defarted of the services of 00, 000 defarts have Foor F

DECK VINT DECK COVERING ON 98 THE FIR PUWOOD ON 21-29 JUISTO @ 10" O.C. 98 THE FIR PUWOOD ON

## TYPICAL CROSS SECTION

